

2D Image handheld scanner XL-3200



- ◎ Decode most popular 1D and 2D barcodes with quick and accurate performance
- ◎ The work environment for retail, healthcare and public sector
- ◎ Full featured and fast, crafted for POS devices to capture various kinds of high-density barcodes
- ◎ Support multiple interface options, USB HID, Virtual COM and RS-232
- ◎ Supports free to switch between handheld and auto-detection mode



| | | | |
|-----------------------|---|---------------------|--------------------------|
| Image Sensor | CMOS | Dimension | L × W × H:175×73×102(mm) |
| Image Size | 640× 480 pixels | Weight | 229g |
| Light Source | Red light,LED | Material | ABS+PC |
| Precision | 4mil | Voltage | DC 5V |
| Depth of Scan Field | 40~220mm(0.33mm pcs0.9,EAN13) | Current (Working) | 230mA |
| Sensitivity | Roll:360° Skew:±50°, Pitch:±50° | Operate Temperature | - 10°C to 55°C |
| Support Interface | USB and RS232, VCP | Storage Temperature | - 40°C to 80°C |
| Print Contrast Signal | 15% | Humidity | 5% to 95% |
| Indicator | Buzzer, LED | Illumination | 0 to 100000LUX |
| Scan Mode | Manual & Continuous & Automatic | Certification | EC (EMC) Class B,Rohs |
| Decoding Capability | 1D: UPC-A; UPC-E; EAN-8; EAN-13; Code39; Codabar; Code128; Interleaved 2 of 5; Industrial 2 of 5; Matrix 2 of 5; Code 93; UCC/EAN 128; Code 11; MSI; UK/Plessey; ISBN/ISSN; GS1 Databar Expanded; GS1 Databar; GS1 Databar Limited. 2D: QR code; PDF 417; Datamatrix | | |



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com